

THERMOMATIC® TVM 60/120

Actuator for rotating mixing valves

Thermomatic TVM is an actuator for control of rotating mixing valves. Its modern design gives silent and reliable function. The actuator features a valve position indicator and LEDs that show the direction of rotation.

The actuator can also be turned manually and has an integrated anti-lock device.

Thermomatic TVM is easy to install and completely maintenance-free.



TECHNICAL DATA



Operating time:	60/120 s
Torque:	5 Nm
Turn angle:	90°
Control type:	3-point
Voltage:	230 V
Power consumption:	<4 VA
IP code:	IP 42
Safety class:	II

Scope of delivery

Article 12 50 01 / 12 50 03

- Thermomatic TVM actuator
- Actuator installation kit (see table on the right)
- Power cable for 230 V AC, pre-installed, 2 m with plug

TVM is suitable for the following mixing valves.

	
ASCAVMSA*	Termoventiler, Esbe, Seltron, Somatherm, Acaso, IVAR, PAW, Hora, BRV, IMIT, Barberi, Olymp, Hoval, Vexve, LK (5 Nm)
ASCAVMSC	Centra DR/ZR
ASCAVMSD	Centra DRU
ASCAVMSE	Siemens VBI/VBF/VBGVCI
ASCAVMSF	Meibes, Wita
ASCAVMSG*	Esbe VRG/VRB
ASCAVMSH	FIRST Rotomix, Rotodivert

* = standard

THERMOMATIC®
by  Termoventiler